



Standard Tubular Motor

Security

"presence simulation function" Makes your home doesn't looks like no one at home.



Privacy

Prevent Prying Eyes



Energy Save

Makes your curtain automatic adjust when Brightness and temperature changing.



Timer

(FTR1018-TM, FTR1530-TM, FTR2523-TM)

Memory Set Functions, 16 Comments Per day, Remote control Compatible



Spec	FTR 1014	FTR 1032	FTR 1530	FTR 4015
Normal torque (Nm)	10Nm	10Nm	15Nm	40Nm
Normal Speed (rpm)	14rpm	32rpm	32rpm	15rpm
N. Supply voltage (V)	230V	230V	230V	230V
Norminal torque (watts)	106W	106W	200W	198W
Rated current (amps)	0.46A	0.46A	0.89A	0.86A
Tempearture	4min	4min	4min	4min
Protection index	IP44	IP44	IP44	IP44



Applied for motorized roller blinds, motorized awnings, motorized projection screen and garage etcComposes by five parts : stator&rotor / brake / planet gearbox, limir switch and built-in radio, receiver (Frequency: 433,92MHz); Small size,low weight, weak voice, precision journey positioning, easy installation. Motor have self- protection function when exact- hot, it will stop work when motor continuous working time is reaching 4- 6minits and motor tube temperature is over 110°C. motor will stop running around 3- 10mints, and get right working when recovered.